

Check back often for updates. If the ballast you are looking for is not on this list, please contact us, and we will make every effort to evaluate compatibility.

Note: Slight flickering or dim startup of the lamp is common, and lamp performance stabilizes within 2-3 seconds.

Note: Reduced Lamp Load is defined as (1) lamp performance on a 2 lamp ballast & (3 or 2) lamp performance on a 4 lamp ballast.

☒ Yes
 ☐ N/A
 ☒ No




Ballast Description			Nominal Lamp Load		Reduced Lamp Load	
Brand	Part Number	Number of Lamps	Input Voltage		Input Voltage	
			120V	277V	120V	277V
Keystone	KTEB-254HO-UV-PS-SL	2	✓	✓	✓	✗
	KTEB-254HO-UV-PS/A	2	✓	✓	✓	✓
	KTEB-454HO-UV-PS	4	✓	✓	✓	✓
Advance	EL1/254A26	2	✓	✓	✓	✓
	HCN-4S54-2LS-H	2	✗	✗	✗	✗
	ICN-2S54 (Version B)	2	✓	✓	✓	✓
	ICN-2S54-N	2	✓	✓	✓	✓
	ICN-2S54-T	2	✓	✓	✓	✓
	ICN-2S54-90C-N	2	✓	✓	✓	✓
	ICN-2S54-90C-SC	2	✓	✓	✓	✓
	IOP-2PSP54-SC	2	✗	✗	✗	✗
	IZT-2S54-D*	2	✓	✓	—	—
	ICN-2S54-D (Version B)	2	✓	✓	✓	✓
	ICN-4S54-90C-2LS-G	4	✓	✓	✓	✓
	IOP-4PSP54-2LS-G	4	✗	✗	✗	✗
Espen	VE454MVHRP	4	✓	✓	✓	✓
Fulham	WH5-120-L	2	✗	—	✗	—
	RHA-UNV-254-LT5	2	✓	✓	✓	✓
	RHA-UNV-454-LT5	4	✗	✗	✓	✓
Fusion	FB254T5MVE	2	✓	✓	✓	✓
	FB454T5MVE	4	✓	✓	✓**	✓**

*Reduced Dimming Range; **Reduced Lamp Load only includes 3 lamps

1. Reduced lamp load is defined as (1) lamp performance on a 2 lamp ballast and (3 & 2) lamp performance on a 4 lamp ballast.
2. SmartDrive LED lamp compatibility is determined when ballast turns on LED lamp and the electrical characteristics of the LED lamp are stable and within designed operating specifications.
3. Keystone SmartDrive LED lamp compatibility does not make any guarantees of electrical performance or lifetime for ballasts listed on this chart that are not manufactured by Keystone.
4. **Ballast compatibility testing is performed with specific date codes. Please contact Keystone for more information on date code of ballasts tested.**
5. All data subject to change.

Specifications subject to change. Last revised on 5.4.18

Keystone Technologies | North Wales, PA | 800-464-2680 | www.keystonetech.com

 Yes
  N/A
  No

Ballast Description			Nominal Lamp Load		Reduced Lamp Load	
Brand	Part Number	Number of Lamps	Input Voltage		Input Voltage	
			120V	277V	120V	277V
GE	GE254MVPS-D	2	✗	✗	✗	✗
	GE254MVPS90-A	2	✗	✗	✗	✗
	GE454MVPS90-F	4	✗	✗	✗	✗
Halco	EP254HO/PS/MV/MC	2	✓	✓	✓	✓
	EP454HO/PS/MV	4	✓	✓	✓	✓
Luma	BLF254-U	2	✓	✓	✓	✓
Maxlite	SKEU542HOP/SC	2	✓	✓	✓	✓
Osram	QHE 2x54T5HO/ UNV PSN	2	✓	✓	✓	✓
	QT 2x54/ 120PHO-DIM	2	✗	—	—	—
	QTP 2x54T5HO/ UNV PSN	2	✓	✓	✓	✓
	QTP 2x54T5HO/ UNV PSN 80-SC	2	✓	✓	✓	✓
	QTP 2x54T5HO/ UNV PSN HT	2	✓	✓	✓	✓
	QHE 4x54T5HO/ UNV PSN HT SCL	4	✓	✓	✓	✓
	QHE 4x54T5HO/ UNV PSN HT SCL {DOE}	4	✓	✓	✓	✓
	QTP 4x54T5HO/ UNV PSN HT W	4	✓	✓	✓	✓
Pacific	EB-254PRS-U	2	✓	✓	✓	✓
Robertson	PSB454T5MV	4	✓	✓	✓	✓
	PSL254T5MV	2	✓	✓	✓	✗
	PSV254T5IVCD	2	✓	✓	—	—
Sunpark	U-2/ 54T5HO	2	✓	✓	✓	✓
Ultrasave	ER254120MHT-W	2	✓	✓	✓	✓
	ER454120MHT-W	4	✓	✓	✓	✓
Universal	B254PUNV-D	2	✓	✓	✓	✓
	B254PUNVHB-D	2	✓	✓	✓	✓
	B454PUNV-E	4	✓	✓	✓	✓
	B454PUNVHB-E	4	✓	✓	✓	✓

1. Reduced lamp load is defined as (1) lamp performance on a 2 lamp ballast and (3 & 2) lamp performance on a 4 lamp ballast.
2. SmartDrive LED lamp compatibility is determined when ballast turns on LED lamp and the electrical characteristics of the LED lamp are stable and within designed operating specifications.
3. Keystone SmartDrive LED lamp compatibility does not make any guarantees of electrical performance or lifetime for ballasts listed on this chart that are not manufactured by Keystone.
4. **Ballast compatibility testing is performed with specific date codes. Please contact Keystone for more information on date code of ballasts tested.**
5. All data subject to change.

Specifications subject to change. Last revised on 5.4.18

Keystone Technologies | North Wales, PA | 800-464-2680 | www.keystonetech.com

✓ Yes
- N/A
✗ No

Ballast Description			Nominal Lamp Load		Reduced Lamp Load	
Brand	Part Number	Number of Lamps	Input Voltage		Input Voltage	
			347V	480V	347V	480V
Advance	HCN-2S54-90C-WL	2	✓	✓	✓	✓
	HCN-4S54-90C-2LS-G	4	✓	✓	✓	✓
	HCN-4S43-2LS-H	4	✗	✗	✗	✗
Fulsion	FB454347T5E	4	✓	—	✓	—
Osram	QHE 2x54T5HO/347-480PSN HT	2	✓	✓	✓	✓
	QHE 4x54T5HO/347-480 PSN HT SCL	4	✗	✗	✗	✗
	QTP2x54T5HO/347-480PSN HT	2	✓	✓	✓	✓
Symban	SLFE-254 T5HO-347V-90C	2	✓	—	✓	—
	SLFE-454 T5HO-347V-90C	4	✓	—	✓	—
Standard	E254T5HOPS347/ N/ XTRM	2	✓	—	✓	—
	E454T5HOPS347/ N/ XTRM	4	✓	—	✓	—

1. Reduced lamp load is defined as (1) lamp performance on a 2 lamp ballast and (3 & 2) lamp performance on a 4 lamp ballast.
2. SmartDrive LED lamp compatibility is determined when ballast turns on LED lamp and the electrical characteristics of the LED lamp are stable and within designed operating specifications.
3. Keystone SmartDrive LED lamp compatibility does not make any guarantees of electrical performance or lifetime for ballasts listed on this chart that are not manufactured by Keystone.
4. **Ballast compatibility testing is performed with specific date codes. Please contact Keystone for more information on date code of ballasts tested.**
5. All data subject to change.

Specifications subject to change. Last revised on 5.4.18

Keystone Technologies | North Wales, PA | 800-464-2680 | www.keystonetech.com