



# KTL-F28T5-841-HE

## T5 LINEAR FLUORESCENT LAMP



### DESCRIPTION

28W T5 | 4100K | 85 CRI | High Efficiency

<b>LAMP TYPE:</b> Linear
<b>BULB TYPE:</b> T5
<b>BASE TYPE:</b> G5 (Miniature Bi-Pin)
<b>WATTAGE:</b> 28W
<b>COLOR TEMPERATURE:</b> 4100K
<b>COLOR RENDERING INDEX (CRI):</b> 85
<b>WARRANTY:</b> 3 Year System/2 Year Standard



### PRODUCT FEATURES

- Low Mercury (2.5mg)
- TCLP Compliant
- Complies with IEC-61195

### OPERATING SPECIFICATIONS


#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens <sup>1</sup>	2900
Mean Lumens <sup>2</sup>	2725
Lumen Maintenance	94%
Efficacy	104 lm/w


#### RATED AVERAGE LIFE

Ballast Type	3 Hours/Start	12 Hours/Start
Program Start	24,000 Hours	30,000 Hours

#### SPECTRAL DISTRIBUTION




#### LUMEN MAINTENANCE



<sup>1</sup> Approximate initial lumens. Lumen output based upon performance after 100 hours of operating life. Measurements obtained during operation using a reference ballast under standard laboratory conditions at 35°C.  
<sup>2</sup> Approximate mean lumens. Lumen output based upon performance at 40% of the lamp's rated average life. Measurements obtained during operation using a reference ballast under standard laboratory conditions at 35°C.

### PHYSICAL SPECIFICATIONS

#### LAMP DIMENSIONS



	Min.	Max.
A (Base to Base)	N/A	45.24"
B (Base to End of Opposite Pin)	45.42"	45.51"
C (End of Pin to End of Pin)	N/A	45.79"
D (Bulb Diameter)	0.61"	0.63"

**NOMINAL LENGTH:** 48"  
**BASE TYPE:** G5 (Miniature Bi-Pin)



# KTL-F28T5-841-HE

## T5 LINEAR FLUORESCENT LAMP

### ORDERING INFORMATION

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS
KTL-F28T5-841-HE-DP	Distributor Pack (Individually Sleeved)	25	Active

### CATALOG NUMBER BREAKDOWN

# KTL-F28T5-841-HE-DP

