

SINCE 1945  
**KEYSTONE**  
LIGHT MADE EASY®



# SENTINEL

WALL MOUNT CYLINDER

With  
**optic**  **swap**

**Form**  **FIT**



# 81 SKUS IN ONE

3 INCLUDED REFLECTORS  
3 DIRECTIONAL OPTIONS

3 POWER OUTPUTS  
3 COLOR TEMP OPTIONS



3"

4"

6"

**YOUR CHOICE OF FINISH:**

All sizes available in Bronze, White, & Black



IP65 RATED

BUILT-IN  
DUSK-TO-DAWN  
PHOTOCELL



25°  
Beam Angle


40°  
Beam Angle

60°  
Beam Angle

optic▷swap

**TOOL-FREE  
CHANGEABLE OPTICS**

To swap optics, unscrew cap, take out the pre-installed 40° reflector, and install one of the other two included reflectors. Screw the cap back on, and you're done.



**MULTIPLE BEAM ANGLES**

40° reflector (pre-installed)  
25° & 60° reflectors (included)  
15° reflector (sold separately)

FormFIT

**CHANGE THE AESTHETIC  
IN SECONDS**

An innovative design feature that transforms the aesthetics of Keystone fixtures with shell accessories that fit on or over the existing fixture.



Black

White

Unpainted



UP ONLY LIGHTING



DOWN ONLY LIGHTING



50/50 LIGHTING

# Sentinel Wall Mount Cylinders

SCAN QR CODE  
to learn more





| CATALOG NUMBER                      | DESCRIPTION    | HOUSING COLOR | SELECTABLE WATTAGE | SELECTABLE CCT | LUMENS | EFFICACY | INPUT VOLTAGE | DIMMING | CRI  | RATED LIFE |
|-------------------------------------|----------------|---------------|--------------------|----------------|--------|----------|---------------|---------|------|------------|
| KT-CYLED36PS-6A-WDI-OSG-8CSB-VDIM   | 6 in. Cylinder | Bronze        | 36W                | 30K/40K/50K    | 3200   | 105 lm/W | 120-277V      | 0-10V   | > 80 | 50,000 hrs |
|                                     |                |               | 28W                |                | 2750   |          |               |         |      |            |
|                                     |                |               | 21W                |                | 2210   |          |               |         |      |            |
| KT-CYLED36PS-6A-WDI-OSG-8CSB-VDIM-W |                | White         | 36W                | 3200           |        |          |               |         |      |            |
|                                     |                |               | 28W                | 2750           |        |          |               |         |      |            |
|                                     |                |               | 21W                | 2210           |        |          |               |         |      |            |
| KT-CYLED36PS-6A-WDI-OSG-8CSB-VDIM-B |                | Black         | 36W                | 3200           |        |          |               |         |      |            |
|                                     |                |               | 28W                | 2750           |        |          |               |         |      |            |
|                                     |                |               | 21W                | 2210           |        |          |               |         |      |            |
| KT-CYLED20PS-4A-WDI-OSG-8CSB-VDIM   | 4 in. Cylinder | Bronze        | 20W                | 30K/40K/50K    | 2050   | 108 lm/W | 120-277V      | 0-10V   | > 80 | 50,000 hrs |
|                                     |                |               | 16W                |                | 1650   |          |               |         |      |            |
|                                     |                |               | 12W                |                | 1290   |          |               |         |      |            |
| KT-CYLED20PS-4A-WDI-OSG-8CSB-VDIM-W |                | White         | 20W                | 2050           |        |          |               |         |      |            |
|                                     |                |               | 16W                | 1650           |        |          |               |         |      |            |
|                                     |                |               | 12W                | 1290           |        |          |               |         |      |            |
| KT-CYLED20PS-4A-WDI-OSG-8CSB-VDIM-B |                | Black         | 20W                | 2050           |        |          |               |         |      |            |
|                                     |                |               | 16W                | 1650           |        |          |               |         |      |            |
|                                     |                |               | 12W                | 1290           |        |          |               |         |      |            |
| KT-CYLED10PS-3A-WDI-OSG-8CSB-VDIM   | 3 in. Cylinder | Bronze        | 10W                | 30K/40K/50K    | 1050   | 105 lm/W | 120-277V      | 0-10V   | > 80 | 50,000 hrs |
|                                     |                |               | 8W                 |                | 840    |          |               |         |      |            |
|                                     |                |               | 6W                 |                | 620    |          |               |         |      |            |
| KT-CYLED10PS-3A-WDI-OSG-8CSB-VDIM-W |                | White         | 10W                | 1050           |        |          |               |         |      |            |
|                                     |                |               | 8W                 | 840            |        |          |               |         |      |            |
|                                     |                |               | 6W                 | 620            |        |          |               |         |      |            |
| KT-CYLED10PS-3A-WDI-OSG-8CSB-VDIM-B |                | Black         | 10W                | 1050           |        |          |               |         |      |            |
|                                     |                |               | 8W                 | 840            |        |          |               |         |      |            |
|                                     |                |               | 6W                 | 620            |        |          |               |         |      |            |


Chart shows wattages and lumen values at full power with up and down light enabled


## Square Shells (Sold separately)

| CATALOG NUMBER          | HOUSING COLOR | DESCRIPTION                        |
|-------------------------|---------------|------------------------------------|
| KT-CYLED-6A-SQ-1-KIT    | Bronze        | Used on 6 in. wall mount cylinders |
| KT-CYLED-6A-SQ-1-KIT-W  | White         |                                    |
| KT-CYLED-6A-SQ-1-KIT-B  | Black         |                                    |
| KT-CYLED-6A-SQ-1-KIT-U* | Unpainted*    |                                    |
| KT-CYLED-4A-SQ-1-KIT    | Bronze        | Used on 4 in. wall mount cylinders |
| KT-CYLED-4A-SQ-1-KIT-W  | White         |                                    |
| KT-CYLED-4A-SQ-1-KIT-B  | Black         |                                    |
| KT-CYLED-4A-SQ-1-KIT-U* | Unpainted*    |                                    |
| KT-CYLED-3A-SQ-1-KIT    | Bronze        | Used on 3 in. wall mount cylinders |
| KT-CYLED-3A-SQ-1-KIT-W  | White         |                                    |
| KT-CYLED-3A-SQ-1-KIT-B  | Black         |                                    |
| KT-CYLED-3A-SQ-1-KIT-U* | Unpainted*    |                                    |

  
**Black**

  
**White**

  
**Bronze**

  
**Unpainted**

\* Custom paint colors for unpainted finishes will have specified lead times.

## 15° Reflector (Sold separately)

| CATALOG NUMBER          | SIZE           | DESCRIPTION                                     |
|-------------------------|----------------|---|
| KT-CYLED-REFL-3A-15-KIT | 3 in. Diameter | 15° Reflector used on appropriate fixture sizes |
| KT-CYLED-REFL-4A-15-KIT | 4 in. Diameter |   |
| KT-CYLED-REFL-6A-15-KIT | 6 in. Diameter |   |



LIT-SS-CYLINDER WALL