

SINCE 1945  
**KEYSTONE**  
LIGHT MADE EASY®



**DIRECT DRIVE D2**    
**8' TYPE B LAMP**

# Selectable 8' Type B Lamps

## Available in two options:

Two 4' sections

8' lamp



### Simple Linking

Connects quickly and installs easily with snug-locking collar and clip, ensuring a rigid presentation

## Easier handling, more versatility

Our selectable Type B Lamps give you the ability to select power output and color temperature, while helping to eliminate the damage issues that can affect 8-foot lamps in transit and installation.

### Selectable Options

3 Wattages - 24/32/40W  
5 CCT - 30/35/40/50/6500K

### Included Cap Adapters

For HO applications using R17d or Fa8, simplifying stocking and installation



### Bypass the Ballast

Connect directly to power for reliable, low-maintenance, and energy-efficient illumination

### Compatible with Tube Ready Fixture

Works with Keystone's Strip Tube Ready Fixture, which includes pre-wired sockets



## Two 4' Type B Tubes | Power and Color Select | 120-277V

SCAN QR  
for more info



CATALOG NUMBER	SELECTABLE WATTAGE	SELECTABLE CCT	LUMENS	EFFICACY	GLASS CONSTRUCTION	INPUT CURRENT	BEAM ANGLE	POWER FACTOR	CRI
KT-LED40PST8-D48G-8CSJ-D2	40W	3000K	5200	130 lm/W	Glass	0.33 @ 120V 0.14 @ 277V	210°	> 0.9	> 80
		3500K	5200	130 lm/W					
		4000K	5500	138 lm/W					
		5000K	5500	138 lm/W					
		6500K	5500	138 lm/W					
	32W	3000K	4200	131 lm/W					
		3500K	4200	131 lm/W					
		4000K	4400	138 lm/W					
		5000K	4400	138 lm/W					
		6500K	4400	138 lm/W					
	24W	3000K	3300	138 lm/W					
		3500K	3300	138 lm/W					
		4000K	3500	146 lm/W					
		5000K	3500	146 lm/W					
		6500K	3500	146 lm/W					
KT-LED40PST8-D48GC-8CSJ-D2	40W	3000K	5200	130 lm/W	Glass Coated	0.33 @ 120V 0.14 @ 277V	210°	> 0.9	> 80
		3500K	5200	130 lm/W					
		4000K	5500	138 lm/W					
		5000K	5500	138 lm/W					
		6500K	5500	138 lm/W					
	32W	3000K	4200	131 lm/W					
		3500K	4200	131 lm/W					
		4000K	4400	138 lm/W					
		5000K	4400	138 lm/W					
		6500K	4400	138 lm/W					
	24W	3000K	3300	138 lm/W					
		3500K	3300	138 lm/W					
		4000K	3500	146 lm/W					
		5000K	3500	146 lm/W					
		6500K	3500	146 lm/W					

## 8' Type B Tubes | Power and Color Select | 120-277V

CATALOG NUMBER	SELECTABLE WATTAGE	SELECTABLE CCT	LUMENS	EFFICACY	GLASS CONSTRUCTION	INPUT CURRENT	BEAM ANGLE	POWER FACTOR	CRI
KT-LED40PST8-D96G-8CSJ-D2	40W	3000K	5200	130 lm/W	Glass	0.33 @ 120V 0.14 @ 277V	210°	> 0.9	> 80
		3500K	5200	130 lm/W					
		4000K	5500	138 lm/W					
		5000K	5500	138 lm/W					
		6500K	5500	138 lm/W					
	32W	3000K	4200	131 lm/W					
		3500K	4200	131 lm/W					
		4000K	4400	138 lm/W					
		5000K	4400	138 lm/W					
		6500K	4400	138 lm/W					
	24W	3000K	3300	138 lm/W					
		3500K	3300	138 lm/W					
		4000K	3500	146 lm/W					
		5000K	3500	146 lm/W					
		6500K	3500	146 lm/W					
KT-LED40PST8-D48GC-8CSJ-D2	40W	3000K	5200	130 lm/W	Glass Coated	0.33 @ 120V 0.14 @ 277V	210°	> 0.9	> 80
		3500K	5200	130 lm/W					
		4000K	5500	138 lm/W					
		5000K	5500	138 lm/W					
		6500K	5500	138 lm/W					
	32W	3000K	4200	131 lm/W					
		3500K	4200	131 lm/W					
		4000K	4400	138 lm/W					
		5000K	4400	138 lm/W					
		6500K	4400	138 lm/W					
	24W	3000K	3300	138 lm/W					
		3500K	3300	138 lm/W					
		4000K	3500	146 lm/W					
		5000K	3500	146 lm/W					
		6500K	3500	146 lm/W					

LIT-8FT TYPE B LAMP-SELL SHEET