



KT-EMRG-650-CFL2

EMERGENCY BALLAST



PRODUCT FEATURES

INPUT VOLTS: 120/277V, 60Hz	LIGHT OUTPUT: 650 Lumen	BATTERY: 3.6V Sealed NiCD
	ILLUMINATION TIME: 90 Minutes	WARRANTY: 5 Years

OPERATING DETAILS

- For use in new or existing fixtures, with or without an AC ballast, where emergency lighting is needed.
- Operates one lamp in the emergency mode.
- 2-in-1 LED indicator light and push-to-test switch (for mandated code compliance testing).
- Internal battery automatically connects to the fluorescent lamp for minimum 90 minute emergency illumination via an internal solid-state transfer switch.
- A discharged battery completely recharges in 24 hours, via a fully automatic solid-state, two-rate charger.

LAMP COMPATIBILITY

- Compatible with most one-, two-, three-, and four-lamp electronic, standard and dimming AC ballasts.
- Operates the following lamps under emergency power:

	2-Pin CFL (W)
No. of Lamps	1
Wattage	13-26

PHYSICAL SPECIFICATIONS

CASE DIMENSIONS

	LENGTH	9.50"
	WIDTH	2.40"
	HEIGHT	1.50"
	CASE MATERIAL:	Painted Steel (White Finish)
	ADDITIONAL FEATURES:	2' Flex Conduit on Both Ends of Ballast

INITIAL LUMEN OUTPUT

LAMP	INITIAL LUMENS
	1-Lamp
2-Pin PL CF 13W	380
2-Pin PL CF 18W	550
2-Pin PL CF 26W	650



KT-EMRG-650-CFL2

EMERGENCY BALLAST

MOUNTING


- UL listed for factory or field installation. Suitable for damp location.
- Can be mounted inside, on top, or remote from the fixture.*
- Designed to be used in both switched and unswitched fixtures.

** When battery packs are remote mounted, the remote distance cannot exceed 1/2 of the distance from ballast to lamp specified by the AC ballast manufacturer. The maximum allowable remote mounting distance is 50 feet.*

ORDERING INFORMATION

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS
KT-EMRG-650-CFL2-DP	Distributor Pack	1	Quick Ship

CATALOG NUMBER BREAKDOWN



Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State codes.