



KTL-FC8T9-DL

T9 CIRCULAR FLUORESCENT LAMP

T9 CIRCLINE
FLUORESCENT LAMP

DESCRIPTION

22W T9 | 6500K | 76 CRI

LAMP TYPE: Circline
BULB TYPE: T9
BASE TYPE: G10q (4-Pin)
WATTAGE: 22W
COLOR TEMPERATURE: 6500K
COLOR RENDERING INDEX (CRI): 76
WARRANTY: 3 Year System/2 Year Standard

PRODUCT FEATURES

- TCLP Compliant
- Complies with IEC-61199, IEC-60901

OPERATING SPECIFICATIONS

PHOTOMETRIC CHARACTERISTICS


Initial Lumens ¹	980
Mean Lumens ²	805
Lumen Maintenance	82%
Efficacy	45 lm/w

RATED AVERAGE LIFE

Ballast Type	3 Hours/Start	12 Hours/Start
Rapid Start	10,000 Hours	N/A*

* 12 Hours/Start not relevant to typical residential applications.

LUMEN MAINTENANCE




¹ Approximate initial lumens. Lumen output based upon performance after 100 hours of operating life. Measurements obtained during operation using a reference ballast under standard laboratory conditions at 25°C.

² Approximate mean lumens. Lumen output based upon performance at 40% of the lamp's rated average life. Measurements obtained during operation using a reference ballast under standard laboratory conditions at 25°C.

PHYSICAL SPECIFICATIONS

LAMP DIMENSIONS



	Min.	Max.
A (Inner Diameter 1)	5.87"	6.06"
B (Inner Diameter 2)	5.83"	6.02"
C, D (Outer Diameter)	8.09"	8.29"
E (Bulb Diameter)	1.10"	1.18"

NOMINAL OUTER DIAMETER: 8"

BASE TYPE: G10q (4-Pin)



KTL-FC8T9-DL

T9 CIRCULAR FLUORESCENT LAMP

ORDERING INFORMATION

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS
KTL-FC8T9-DL-DP	Distributor Pack (Individually Sleeved)	12	Active

CATALOG NUMBER BREAKDOWN

KTL-FC8T9-DL-DP

